



For 1/4", 3/8" and 1/2" Hose I.D.

B-Series Industrial Grade for Professional Use

B-Series all steel hose reels are designed for industrial applications where heavy usage also needs a small footprint to accommodate. Built on a smaller scale with the same components as our workhorse C series reels, this reel's compact design fits easily into restricted space areas. Heavy gauge base with no welds or bolts, this product will give years of dependable service in high use applications. With a carbon steel outlet swivel and fluid shaft, the reels are available for use in low pressure (300psi), medium pressure (2,000psi) and high pressure (5000psi) applications for air, water, oil, and grease.

This product is ideal where hose storage and operating efficiency are needed. Full flow 1/2" shaft allows maximum delivery to the application point. Four position guide arm allows easy adjustment to the position best suited.

Product Name:

Hosetract B-Series Low/Medium/High Pressure

Manufacturer:

Hosetract Industries Inc. 6433 Discount Drive Fort Wayne, IN 46818 www.hosetract.com


Swivel:

Standard: Carbon Steel zinc coated

Features:

- Powder Coat finish
- Mounting Slots 3/8" wide x 3/4" deep for max 5/16" dia. bolt
- Safety banded spring sealed springcase
- Full 1/2" flow path (Low and Medium pressure models)
- Compact design
- Reels shipped standard front hose payout position.
- Nonsparking latch mechanism

Inlet - 1/4" FPT (All HB) - 1/2" FPT (All LB, MB)



3/8" wide x 3/4" deep for max 5/16" dia. bolt

Standard front payout position





For 1/4", 3/8" and 1/2" Hose I.D.

TECHNICAL

DATA SHEET

B SERIES Model # Weight PSI **Hose Capacity ID** Hose Capacity ft **Reel Inlet Reel Outlet** LB-200 1/2" NPT (F) 3/8" NPT (F) 25 1000 1/4″ 50' 1/2" NPT (F) 1/2" NPT (F) LB-300 1000 3/8″ 35' 25 1/2" NPT (F) 1/2" NPT (F) LB-500 25 1000 1/2" 25' 1/2" NPT (F) 1/2" NPT (F) MB-300 22 3000 3/8" 35' 1/2" NPT (F) MB-500 23 3000 1/2" 25′ 1/2" NPT (F) HB-200 25 5000 1/4″ 1/4" NPT (F) 1/4" NPT (F) 35' 1/4" NPT (F) 3/8" NPT (F) 25 HB-300 5000 3/8" 25′

Models with hose and hose stop						
Model #	Weight	PSI	Hose ID	Hose Length ft	Reel Inlet	Hose End Fitting
AW (Air/Water)		Low Pressure				
LB-250 ★	29	300	1/4″	50'	1/2" NPT (F)	1/4" NPT (M) *
LB-335 ★	32	300	3/8″	35′	1/2" NPT (F)	1/4" NPT (M) *
LB-525 ★	32	300	1/2″	25′	1/2" NPT (F)	1/2" NPT (M) *
LU (Lubricants)		Medium Pressure				
MB-335	31	3000	3/8″	35′	1/2" NPT (F)	3/8" NPT (M) *
MB-525	31	2750	1/2″	25′	1/2" NPT (F)	1/2" NPT (M) *
GR (Grease)		High Pressure				
HB-235	33	5000	1/4″	35′	1/4" NPT (F)	1/4" NPT (M) *
HB-325	34	5000	3/8″	25′	1/4" NPT (F)	3/8" NPT (M) *

* Can be furnished with different sizes upon request.

★: Comes with inlet hose assembly

ACCESSORIES:

Hose Stop Assemblies



1234A - 1/4" **1233A -** 3/8" **1232A -** 1/2"